

# THE PREDATOR® 600 PORTABLE AIR SCRUBBER

## Big Time Performance in a Small Package

### INCREDIBLY LIGHTWEIGHT AND COMPACT

Weighs just 38 lbs., including filters.

### POWERFUL

Variable-speed airflow, rated at 200 cfm to 600 cfm.

### SPECIAL CABINET RESIN

High-density polyethylene resin contains microbial growth and UV inhibitors. And, the Tefgard® finish makes the PRED600 easier to clean and decontaminate after the job is done.

### EFFECTIVE FILTRATION

Comes with two pre-filters and a True 99.97% HEPA filter. VAPOR-LOCK® carbon pre-filter for odors is optional.

### ECONOMICAL TO OPERATE

Filters that last longer and cost less, so you can save thousands of dollars in replacement filter costs.

### SECURE STACKING

Multiple units nest securely together, to save space when stacked in a warehouse, a van, or in use on the job.

### LOW AMPERAGE DRAW

Up to five PREDATOR 600 units can be safely daisy-chained on one 15-amp circuit

### SAFETY FIRST

ETL-certified to meet stringent UL and CSA standards for electrical safety and flammability.

### ORDER NOW

Call us today at 800-634-9091 (US) or 800-827-6443 (Canada) to place your order or to find out more.



United States: 800-634-9091  
Canada: 800-827-6443  
Overseas: 678-889-4200  
[www.abatement.com](http://www.abatement.com)

# PREDATOR® 600 SPECIFICATIONS AND PRODUCT FEATURES

**NET WEIGHT WITH FILTERS:**

38 pounds

**SHIPPING WEIGHT:**

43 pounds

**DIMENSIONS (LxWxH):**

24" L x 18" W x 19 1/2" H

**POWER SUPPLY REQUIREMENTS:**

120 volts AC, 60Hz, 15 amps

**NORMAL OPERATING AMPS:**

2.5 A or less (Daisy-chain up to five units on one 15A circuit)

**MOTORIZED IMPELLER:**

Motorized impeller with thermal overload protection, auto re-set, 60Hz, single phase

**CIRCUIT BREAKER:**

12 amp

**POWER CORD:**

25 ft. long grounded power cord with cord wrap clip

**CABINET MATERIAL:**

UL94HB flame retardant resin with EPA-Registered microbial inhibitor and uv inhibitor

**TRANSPORTABILITY:**

Sturdy transport handle

**PRE-FILTER ACCESS:**

Easy-operating hinged door secured by rotating latches, with a gasket to protect against filter by-pass

**FILTERS:**

Stage 1 pre-filter - 1" coarse particulate pre-filter

Stage 2 pre-filter - 2" pleated particulate pre-filter

Optional Stage 2 Vapor-Lock® carbon filter

True HEPA filter - Tested and certified to an efficiency of 99.97% or higher against 0.3 micron size particles

